

## Application Note

# Determination of alcohol content in Australian red wine by Alcohol meter

Industry	:	Food and Beverage
Instrument	:	Alcohol meter
Measurement method	:	Resonant frequency oscillation

## 1. Scope

This is an example about determination of the alcohol content (vol%), specific gravity (t/t) and density (g/cm<sup>3</sup>) in Australian red wine. The alcohol meter can be used enough for determination of these applications on the wine making process.

Technical note: The alcohol sample must be distilled as per the procedure specified on local regulations before the alcohol content can be measured with this alcohol meter.

## 2. Apparatus

- Alcohol meter ALM-155
- Distillation apparatus



## 3. Sample

- Australian red wine

## 4. Reagent

- Pure water for rinsing

## 5. Procedure

A: Alcohol content (vol%):

- 1) Take distilled sample solution into beaker
- 2) Introduce the sampling nozzle into the beaker
- 3) Press [Meas.] button on the instrument

B: Specific gravity (t/t) and Density (g/cm<sup>3</sup>):

- 1) Take wine sample solution into beaker
- 2) Introduce the sampling nozzle into the beaker
- 3) Press [Meas.] button on the instrument

## 6. Measurement results

	Procedure A		Procedure B
	Alcohol (vol%) at 20°C	S.G. (t/t)	Density (g/cm <sup>3</sup> )
1	13.65	0.99701	0.99523
2	13.65	0.99705	0.99527
3	13.65	0.99701	0.99523
Mean	13.65	0.99702	0.99524
SD	0.00	0.00	0.00
RSD(%)	0.00	0.00	0.00